

Datasheet

TRK 19060 SG

Metal Grade Stick

T-ISS

Product description

TRK 19060 SG Stick Grade Metal is a specially packaged rapid curing synthetic metal repair compound for on-site repairs to metal components such as leaking pipes, tanks, ducts, radiators, etc.

Suitable for emergency repairs or part of planned maintenance to equipment such as; worn or damaged pump shafts, cracked pump or valve casings, scored hydraulic rams, worn bearing housings, damaged flanges, leaking tank seams, worn keyways, cracked engine blocks, etc.

Pictures



Product features & numbers

- Simple to use; only requiring simple hand mixing to activate reaction between the concentrically packed components
- Designed for application by gloved hand, putty knife or spatula
- Can be applied to any damaged metal surface, plus glass, fiberglass and other composite surfaces
- Designed for rapid repairs to cracked casting, leaking pipes, tanks, flanges, etc., minimizing downtime
- Exhibits excellent adhesion to correctly prepared metal surfaces

Art. Nr.: TRK 19060 SG HS Code: 39073000 IMPA: 81.22.02.

Additional product information

When the product is fully mixed it has an useable life of 3-5 minutes at 20°C.

Heat Resistance:

Suitable for long-term water immersion at temperatures up to 140°C

Packed: 1
Sales Quantity: 10 x 1

Applications & Use

Surface Preparation:

All oil, loose material and grease must be removed from the surface. The material is suitable for application to manually prepared surfaces.

Mixing & Application:

The product is supplied in stock form and therefore the Base and Activator components are pre-measured. Simply break off the required amount of material from the stick and using gloved hands, knead the product until the black and grey components become a consistent mid grey.

Specifications

Shelf Life:

5 years if unopened and store in normal dry conditions (15-30°C).

Useable life:	5 minutes
Hard dry:	30 minutes
Machining & light loading:	30 minutes
Full loading:	1 hour
Immersion:	1 hour