

中国船级社 CHINA CLASSIFICATION SOCIETY

证书编号/Certificate No. FS18PWA00003

工厂认可证书

CERTIFICATE OF WORKS APPROVAL

兹证明本证书所述制造厂具备按照下列标准的要求生产本证书所列产品的能力和条件。

This is to certify that the manufacturer stated in the certificate meets the requirements of the standards listed below and is available with the ability and conditions to produce the products described in the certificate.

制造厂/Manufacturer

T-ISS BV, the Netherlands

地址/Address

Helmkamp 32-34, 7091HR, Dinxperlo, the Netherlands

产品名称/Product

防溅胶带 **Anti Spray Tape**

附加标志/Notations

无/Nil.

认可标准/Approval Standard

1.1974年《国际海上人命安全公约》及其修正案第II-2章第4条 Regulation 4, Chapter II-2 of International Convention for the Safety of Life at Sea, 1974, as Amended 2. 中国船级社《钢质海船入级规范》(2018)及其修改通报第3篇第4章 Chapter 4, Part Three of China Classification Society Rules for Classification of Sea-going Steel Ships 2018 and its Amendments

用于/Intended for

船舶与海上设施/Ships and Offshore Installations

批准的图纸/Approved Drawings

图纸批准号/ Drawings Approval No.: FS11T00001, FS18PWA00003

产品认可试验报告/ Approval Test Report

试验报告编号/Test Report No.: 20050289 试验报告日期/Test Report Date: 2005-06-21

证书有效期至/This Certificate is valid until

2023年02月02日/Feb. 02,2023

发证机构 中国船级社釜山分社

签发日期

2019年01月28日

Issued by CCS Busan Branch

Jan. 28,2019 Date

本证书提與中间的接往規範學和关規定答文。当本适当包括多页纸张时,则所有证书页为一个整体,必须同时使用。每一页证书均须由本社競車方为有效。证本书复印件无效。任务是自和个人均不思想录或书选本证书的部分内容。有关各方对所持证书的真实性有疑问时,可以向我社检验机构各询。
This Critificate is issued pursuant to the Rules of the Society and related regulation. When the certificate consists of more than one page, all pages of the certificate are taken as a whole and re used imultaneously. No certificate page is valid without bearing the stamp of the Society and no copied form of the certificate is regarded as valid. Any purt of the certificate is not to be extracted or abridged by any unit or individual in any form, Related parties who are doubted about the authenticity of the certificate may inquire of the Society or its offices.

Form No: WORLD Society Of the Society of the Offices.







第1页共3页/Page 1 of 3

试验报告编号/Test Report No.: 2911/07/2005 试验报告日期/Test Report Date: 2005-11-14 试验报告编号/Test Report No.: T2012-303590-004 试验报告日期/Test Report Date: 2012-12-10

认可后的产品检验方式/Module of Product Inspection after Approval

按照规范只认可不进行产品检验的产品/The product approved only in term of the rules: 认可后的产品检验由制造厂按本社批准的产品检验计划进行检验,经检验合格后由制造厂签发合格证明,并连同该产品的本社认可证书复印件一并交付用户,制造厂对产品符合公约、法规、本社规范和本社认可的标准规定负责。 After approval, product inspection should be carried out by the Manufacturer in accordance with the product inspection scheme approved by the Society. Upon satisfactory inspection, and the Quality Certificate issued by the Manufacturer should be provided to the purchaser together with the copy of the approval certificate issued by the Society. The manufacturer should take responsibility for the product being in compliance with the convention, statutory regulation, the Society rules and the standard accepted by the Society.

认可保持条件/ Maintenance Requirements of Approval

1. 工厂认可后,如果图纸、技术文件、工艺规程有较大改变,应征得本社同意。若改变涉及或影响到产品的设计、主要制造材料、关键工艺或产品的特性、特征,则与特性有关的图纸和技术文件应经过本社审批,并在检验机构认为必要时,经本社检验人员到厂进行检查和见证有关试验,其结果应能证实仍符合认可条件。

After works approval, if there are any major changes to the drawings, technical documents, specifications, prior consent should be obtained from the survey office of the Society. If the changes involve or affect product design, major construction materials, key workmanship or product characteristics and properties, drawings and technical documents related to properties are to be examined and approved by the Society and, where deemed necessary by the survey office, the surveyor to the Society will go to the manufacturer to inspect or witness relevant tests and the results of the tests should be able to demonstrate compliance with the approval conditions

2. 工厂的质量管理体系应保持有效运行,并且与认可时一致。如果质量管理体系发生改变,应经原体系认证机构审核并报本社批准。

The quality management system of the factory shall be ensure effective operation, and shall be the same as the situation of approval. If there are any changes to the quality management system, auditing of the original certification organization for quality management system and the society's approval shall be obtained.

3. 工厂认可证书获得者应接受本社每年一次的定期审核,定期审核日为认可证书期满之日对应的每一周年日,检查工作可在定期审核日的前后三个月内进行。Those who have obtained the certificate of works approval shall receive periodical audit done by the Society on an annual basis. The date of periodical audit shall be each anniversary date which corresponds to the date of expiry of the relevant certificate and the periodical audit may be done within a time span of three months before and after the annual surveillance date.

4. 在认可证书有效期内,本社检验人员可在未经事先通知的情况下对工厂的产品制造过程进行审核,以验证产品的生产是否符合业经本社批准的图纸和文件。工厂应予以配合。

Within the validity of the approval certificate, the surveyor to the Society may pay unannounced audit to the manufacturing process of the product in order to confirm whether it is in compliance with the drawings and documents approved by the Society. The factory should provide an active cooperation and necessary for the surveyor.

5. 认可证书有效期内,如果出现可能导致本社暂停或撤消认可的情况,工厂应及时采取有效的纠正措施。 Within the validity of the approval certificate, if cases occur that may cause the Society to suspend or withdraw the certificate, the manufacturer should take corrective actions in a prompt and effective manner.

备注/Remarks

1. 本证书由原型式认可证书(No. FS14T00041)变更并换新。

This certificate is modified and renewed from the previous Type Approval Certificate No. FS14T00041.

2. The product is produced under the licence of T-ISS BV.

3. The product is used for screening of pipe joints and fittings in accordance with SOLAS II-2, Reg b 2.215.4.

4. 本社正市核了产品,无石棉声明,但本社的审核不免除产品厂按照合同关系向订货方保证产品无石棉的责任。
The declaration of asbestos-free submitted by manufacturer has been reviewed by the Society.
However, liability of the manufacturer to guarantee the products are asbestos-free to purchaser under contract will not be exempted.

CLASSIFICATION

国船员

第2页共3页/Page 2 of 3



产品明细/Product Description

防溅胶带/Anti Spray Tape (M001)

名称/Name	属性(值)/Value	单位/Unit
型号/Type	T-ISS SPRAY STOP STANDARD & SPRAY STOP 50+	
产品尺寸/Dimension	0.25mm x 35/50/140/250/500/1000mm x 10M, 0.36mm x 35/50/140/250/500/1000mm x 10M	
材料/Material	Aluminium-fiber sheet, Silicone adhesive, Backing film	
设计压力/Design pressure	1.5 MPa for SPRAY STOP STANDARD; 3.7 MPa for SPRAY STOP 50+	
温度范围/Temperature range	Max. 150°C (Fluid Temp.)	

中国船级社釜山分社 CCS Busan Branch

05 ****本本证书完/ End of Text****



