Datasheet SlipStop Tape



Revision 2020

Product description

T-ISS SlipStop tape is to protect people from incidents by falling down on slippery spots.

Our product would offer safe working places by placing on stairs both indoor and outdoor.

Easy installation & permanent adhesion. Great requirements would also meet your budget with reasonable price.

Abide by Disability Discrimination Act.

Pictures



Dimensions

Our SlipStop Tape, is available in rolls in the following sizes:

Width Length Thickness Weight 50 mm 10 mtr 0,1 mm 0,8 kg 100 mm 10 mtr 0,1 mm 1,5 kg other possible sizes on request

ISSA IMPA HS Code: 6805 3000

Certificates & Standards

• Green Passport

Applications & Use

To be applied to surfaces where there may be a safety hazard due to slippiness either in or out doors.

- ships
- offices
- platforms
- public areas
- * Installation should be undergone proper temperature, between -5 °C up to 50 °C.

Specifications

- Material characteristics:
 - Safety track is a mineral coated plastic film, one side pressure sesitive adhesive, protected by a removable liner.
- Resistance towards water, grease: Excellent
- Adhesion to steel: 1500 g/ 25 mmm
- Holding power: 8 hours/ 20 mm 2 kg
- Tensile strength:6 kg/ 25 mm
- Elongation at break:25 %

