

Datasheet

LIFE RAFT/RESCUE BOAT HOOK PX01

T-ISS

Product description

The T-ISS Life Raft/Rescue Boat Hook is a combined automatic release hook which can handle rescue boats and life rafts up to a safe working load of 35kN.

The advantage of using the T-ISS PX01 is two-fold;

- It will increase safety, as the crew only need to familiarize themselves with one hook, instead of two. Also there is no second hook, dangerously swinging around when lowering. In distress situations the crew will instantly know which hook to use, as there is only one hook.
- Secondly it is economical, why buy two hooks if one is sufficient?

Pictures



Dimensions

Art.no: PX01

Dimensions: 285x260x70 mm

With	Length	Height	Weight
260 mm	285 mm	70 mm	7 kg

HS code: 7326.9090

Certificates & Standards

Approved by:

- EC Directive 96/98EC on Marine Equipment (MED)
Relevant standard:
- LSA Code for Hooks for Life raft Launching, as amended MSC.81(70)
- Fully compliant with updated SOLAS requirements as per Resolutions MSC.320(89) and MSC.321(80)
- Rina No. MED 000816ws/002

Applications & Use

This hook can be used for rescue boats with a davit load less than 3500 kg and/or a davit launched life raft up to 40 pax. The hook can be operated as an automatic release hook, releasing when the craft enters the water, or as a manual release hook, whereby the load needs to be off the hook before releasing.

Specifications

Maximum Safe Working Load: 3500 kg
Material: Stainless steel 316/Duplex