

Datasheet

Heat Prevention Tape

T-ISS

2024

Product description

T-ISS Heat Prevention Spray Tape is a specialized tape used in industrial and marine applications, particularly in situations with high temperatures. It is designed to prevent conduction of temperatures, and can be used between floors and walls or, for instance, on wiring harnesses in an engine room.

Our Heat Prevention Tape is a non flammable tape and has a heat resistance up to 200 degrees, with a strong adhesive property when attached to steel. The tape is made of aluminium foil with acryl adhesive glue.

Pictures

Technical Data & Dimensions

Art. Nr: H ETT050 H ETT100 H ETT150

Elongation: 10%

Colour: Silver

Dimensions: 50 mm x 10m
100mm x 10m
150mm x 10 m

50 mm x 50m
100mm x 50m
150mm x 50 m

HS Code: 3919.1080

Standards

This product passed all tests perfectly according to S AS EG. SE12 FI E TECTI N ATE IA S F CA G SHI S. S AS EG. II 2/5. .2 .

It is applied to ship special marine structrue and everywhere to protect lives and property with superiority.

Complies with No. ED/ .1 a. S AS eg. II 2/ II 2/5 II 2/ / I SC/Circ. 1120 2000 HSC Code and I 2010 FT Code.

Applications & Use

The tape is recommended on connections in the following situations and where temperatures are high:

- Floors and walls
- Steel

Specifications

- Temperature resistance up to 200°C
- Fre retardant
- Excellent adhesion
- High tensile strenght with Glass Cloth