

Datasheet

RESCUE BOAT HOOK PX03

T-ISS

Product description

The PX03 release hook meets high SOLAS standards for release hooks, as specified in MSC.81(70) and the applicable LSA code, and is designed to suspend davit-launched rescue boats with a davit load of up to 1,500 kg.

Pictures



Dimensions

Art.no: RELHK-PX03
Dimensions: 260 x 135 x 60 mm
Weight: 4,5 kg

HS CODE: 73269092
COO: China

Certificates & Standards

Approved by:

- EC Directive 96/98/EC on Marine Equipment (MED)
- Bureau Veritas
- Korean Register No. MED-MB-1283-21 / 1.26a&b

Relevant standard:

- LSA Code for Hooks for Liferaft Launching, as amended MSC.81(70)
- Fully compliant with updated SOLAS requirements as per Resolutions MSC.320(89) and MSC.321(80)
- RINA No. MED 000816ws/002

Applications & Use

Installation of the hook is easy. Disassemble the top shaft by removing the hexagonal securing screw, and unscrewing the nut which holds the shaft in position. Place the spliced eye or corresponding wire rope fall over the distance bush. Place the distance bush between the two side plates and place the shaft. Then make sure the shaft is fastened tightly and the hexagon securing screw is put back in place.

Specifications

Maximum Safe Working Load: 1500 kg
Material: Stainless steel 316 / Duplex

Instructions

The PX03 is a manual release hook: handling can be done by one person, just push the release handle in the upward position and the hook will open.

- Use non-rotating wire rope
- Use a painter line where possible
- Use a shackle \varnothing 19 mm up to \varnothing 27 mm