

# Datasheet

## Heat Prevention Tape

# T-ISS

### Product description

T-ISS Heat Prevention Tape is a specialized tape used in industrial and marine applications, particularly in situations with high temperatures. It is designed to prevent conduction of temperatures, and can be used between floors and walls or, for instance, on wiring harnesses in an engine room.

Our Heat Prevention Tape is a non flammable tape and has a heat resistance up to 200 degrees, with a strong adhesive property when attached to steel. The tape is made of aluminium foil with acryl adhesive glue.

### Pictures



### Dimensions

Art. No: HPRETT050, HRRETT100, HPRETT150

Elongation: 10%

Colour: Silver

Dimensions: 50 mm x 50m  
100mm x 50m  
150mm x 50 m

HS Code: 3919.1080

COO: Korea

### Standards

This product passed all tests perfectly according to SOLAS REG. SE126 FIRE PROTECTION MATERIALS FOR CARGO SHIPS. (SOLAS REG. II-2/5.3 - 6.2).

It is applied to ship, special marine structure and everywhere to protect lives and property with superiority.

Complies with No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code.

### Benefits

The tape is recommended for use on connections in high-temperature environments, such as those found on floors, walls, and steel surfaces.

### Specifications

- Temperature resistance up to 200°C
- Fire retardant
- Excellent adhesion
- High tensile strength with Glass Cloth