

Datasheet

Foamtape

T-ISS

Product description

T-ISS double-coated adhesive foam mounting tape designed for use in permanent applications where high shear and substantial loads may be encountered, even subjected to UV-light, plasticisers and a wide temperature range.

High tack permanent adhesive with excellent endurance and weather resistant properties designed for mounting and joining nameplates, plastic trim, signs and emblems.

Long term bonding performance to plastic hangers and mirror mounting.

Pictures



Dimensions

Our Foamtape, is available in rolls in the following sizes:

Width	Length	Thickness
25 mm	10 mtr	1 mm
50 mm	10 mtr	1 mm
100 mm	10 mtr	1 mm

other possible sizes on request

HS Code: 3919.1019

Certificates & Standards

- Green Passport



Applications & Use

Application:

- Surface must be clean and free from dust and grease.
- Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.
- The indicated level of performance will be reached after a bonding period of 24 hrs at 23 °C.

Use:

- Use fixation of signs, mirrors, profiles to wall surfaces, for example, Pictures.

Specifications

- Peel Adhesion:
PSTC-3 1.8 kg / 25 mm
- Shear Strength:
PSTC-7 Over 72 hrs
- Heat Resistance:
Over 24 hrs
- Service Temperature:
-30 °C ~ 120 °C