

# Datasheet

## SafeSign PVC

# T-ISS

### Product description

Our range of SafeSign PVC signs contains all the major sign categories, eg. Fire fighting signs, fire control plan signs, prohibition signs, escape/lifesaving appliance signs, hazard signs, mandatory/cargo signs and combination signs.

### Image



### Dimensions

T-ISS produces all types of signs according to required standards.

Sizes:

Width	Height	Thickness	Weight
50 mm	50 mm	1,8 mm	0,004 kg
75 mm	150 mm	1,8 mm	0,018 kg
100 mm	300 mm	1,8 mm	0,031 kg
150 mm	150 mm	1,8 mm	0,036 kg
200 mm	150 mm	1,8 mm	0,041 kg
300 mm	150 mm	1,8 mm	0,066 kg
450 mm	150 mm	1,8 mm	0,106 kg

(Other possible sizes on request.)

HS Code : 39199000.99

### Certificates & Standards

- Green Passport
- DNV certificate module B & D
- Compliant with IMO Res. A760(18) as amended ISO 17631:2002.

### Applications & Use

Installation

The recommended height for installation of the SafeSign signs is approx. 160 cm from the floor level.

### Specifications

- Design- Symbols comply with international standards  
Custom made - all text possible
- Quality:  
SafeSign XL  
SafeSign XXL on request
- Photoluminescence
 

SafeSign XL	10 min: 75mcd/m <sup>2</sup>	Decay time: 1250 m
	60 min: 10 mcd/m <sup>2</sup>	

  - XXL performance  
160mcd/10min  
22mcd/60min  
decay 0.3mcd/in 2300min



T +31 (0) 79 330 1000  
Storkstraat 1-3

I t-iss.com  
2722NN Zoetermeer

E info@t-iss.com  
The Netherlands

# T-ISS

Safety Suppliers