

Datasheet

Pneumatic Line Thrower



T-ISS™
safety suppliers

a Heijboer Safety Group company

Product description

The BLT 250 Pneumatic Line Thrower is a pneumatic system that launches projectiles using compressed air.

The BLT 250 features interchangeable launchers and easy-to-refill projectiles. It meets the requirements of SOLAS/IMO Regulation 74/83.

- Projectiles reach approximately 250 meters.
- Projectiles are only affected by crosswinds.
- Projectiles reach their max. speed at the end of the launcher.
- Due to the aerodynamic design, wind has minimal effect on the projectiles.

Product Image



Technical Specifications

Weight / Length:

Throwing Unit:	8.3 kg / 165 cm
Projectile:	2.1 kg / 100 cm
Total Unit:	10.4 kg / 175 cm
Bag Size:	105 × 22 × 20 cm
Total Bag Weight:	21 kg

Shooting Chamber Pressure:	65 bar
Average Nozzle Velocity:	50.6 m/s
Maximum Recoil:	5400 N
Minimum Shots:	4 projectiles
Air Cylinder Pressure:	200 bar
Volume:	2 liters

Certificates and Standards

Approvals

- RINA
- USCG
- Wheelmark

Standards

SOLAS/IMO regulation 74/83

Product Information

Art. no.:	BLT250
HS Code:	84242000
IMPA:	232093
NSN:	1095-22-636-5644

All items are reusable. Shelf life is unlimited, provided that regular maintenance is carried out by authorized service personnel.

The only cost associated with every four launches is refilling the cylinder with dry air.

Features and Contents

The standard set is supplied in a sturdy orange bag. A wooden storage box is optional.

The complete set consists of:

- 1 BLT 250 Throwing Unit
- 4 Projectiles for BLT 250
- 1 Launcher
- 1 User Manual



T-ISS™
safety suppliers

a Heijboer Safety Group company