

Datasheet

Tri Hook Connection Plate

T-ISS

Product description

The T-ISS Tri Hook Connection Plate is designed to safely suspend and organise multiple release hooks, allowing them to remain connected and immediately available for deployment during lifeboat and rescue boat operations. Manufactured from high-strength, corrosion-resistant steel, it provides a secure connection between the davit fall and compatible release hooks using certified shackles.

Fully compatible with the T-ISS PX01 Release Hooks, PX02 Lifteraft Release Hook and PX03 Rescue Boat Hooks, the connection plate has been tested to verify its Safe Working Load (SWL) of 3,500 kg and complies with the stringent requirements of SOLAS and the LSA Code.

Pictures



Dimensions

Article nr: TRIHK-CP

Dimensions: 380 x 290 x 290 mm

Thickness: 15 mm

Weight: 3,65 kg

Material: SS316 Stainless steel

HS code: 73269092

Country of origin: EU/ The Netherlands

Pictures



Usage

The Tri Hook is connected to the liferaft sling and accommodates both a rescue boat hook and a liferaft release hook. It is designed for vessels equipped with both rescue boats and liferafts, allowing the appropriate hook to be used depending on which craft is being launched or recovered. The Tri Hook provides the same functionality as the previous combined two-in-one hook, while offering a more practical and versatile connection solution.

Specifications

